

Caractéristiques techniques : Unité intérieure GAINABLE



Indoor model			MTJ-09HWFNX-QRD1W(GA)	MTJ-12HWFNX-QRD1W(GA)	MTJ-18HWFNX-QRD1W(GA)	MTJ-24HWFNX-QRD1W(GA)
Power supply		V- Ph-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	180	185	200	185
	Current	A	1,1	1,1	1,3	1,2
Heating	Capacity	Btu/h	10000	13000	19000	27000
	Input	W	180	185	200	185
	current	A	1,1	1,1	1,3	1,2
Indoor fan motor	Model		ZKFN-81-8-1	ZKFN-81-8-1	ZKFN-81-8-1	ZKFN-165-10-1L
	Qty		1	1	1	1
	Input	W	-	-	-	/
	Capacitor	uF	-	-	-	/
	Speed (Hi/Mi/Lo)	r/min	1130/1047/965	1140/1052/965	1140/1052/965	950/850/750
Indoor air flow (Hi/Mi/Lo)		m3/h	620/540/450	660/570/470	900/780/650	1200/1000/700
ESP	Rated	Pa	25	25	25	25
	Range	Pa	0-80	0-60	0-100	0-160
Indoor sound pressure level (Hi)		dB(A)	40/34.5/27.5	41/38/34	41/38/34	33.5/32.5/31
Indoor sound power level (Hi)		dB(A)	57	58	60	56
Indoor unit	Dimension(W*D*H)	mm	700x506x200	700x506x200	700x750x245	1000x750x245
	Packing (W*D*H)	mm	860x540x285	860x540x285	925x850x298	1225x860x304
	Net/Gross weight	Kg	16.6/19.8	16.6/19.8	24.4/29	31.8/37.2
Design pressure		MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
Drainage water pipe dia.		mm	ODΦ25	ODΦ25mm	ODΦ25mm	ODΦ25mm
Controller			Wired Control	Wire Control	Wired control	Wired control