

Caractéristiques techniques : Unité intérieure MURAL



Indoor Model			MSGPAU-09HRFN8-QRD6GW	MSGPBU-12HRFN8-QRD6GW	MSGPCU-18HRFN8-QRD6GW	MSGPDU-24HRFN8-QRD6GW
Power supply		V-Ph-Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz	1Ph,220-240V,50Hz
Cooling (Standard conditions)	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	30	30	55	88
	Current	A	0,14	0,14	0.15	0,28
Heating (Standard conditions)	Capacity	Btu/h	10000	13000	19000	25000
	Input	W	30	30	34	62
	Current	A	0,14	0,14	0.15	0.28
Indoor fan motor	Model		ZKFP-30-8-357L	ZKFP-30-8-357L	ZKFP-35-10-188L	ZKFP-58-8-26L
	Input	W	30	30	55	88
	Capacitor	uF	/	/	/	/
	Speed(Hi/Mi/Lo)	r/min	1050/930//870	1000/880/820	1000/868/802	1050/910/840
Indoor coil	a.Number of rows		2	2	2	2
	b.Tube pitch(a)x row pitch(b)	mm	19.5x11.6	19.5x11.6	19.5x11.6	21x13.37
	c.Fin spacing	mm	1.3	1.3	1.3	1.3
	d.Fin type (code)		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	e.Tube outside dia.and type	mm	Φ5,Inner groove tube	Φ5,Inner groove tube	Φ5,Inner groove tube	Φ7,Inner groove tube
	f.Coil length x height x width	mm	530x195x23.2+530x97.5x23.2	620x195x23.2+620x97.5x23.2	770x195x23.2+770x117x23.2	820x231x26.74+820x126x26.74
	g.Number of circuits		3	3	4	4
Indoor air flow (Hi/Mi/Lo)		m3/h	510/360/285	600/450/370	800/600/470	1090/790/635
Indoor noise level (Hi/Mi/Lo/Si)		dB(A)	39/34/25/19.0	39/32/26/20	43/36/28/21.5	46/39.5/32.5/21.5
Indoor sound power level		dB(A)	56	56	58	60
Indoor unit	Dimension(W*D*H)	mm	723x199x286	813x201x289	975x218x308	1055x231x330
	Packing (W*D*H)	mm	780x270x365	870x270x365	1035x295x385	1130x405x310
	Net/Gross weight	kg	7.5/9.6	8/10.4	10.2/13.3	13/16.4
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	6.35mm(1/4in)/12.7mm(1/2in)
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control