

## Specifications

## Mural



Model			MH15QH18	MH22QH18	MH28QH18	MH36QH18
Power supply			1-phase, 220-240V, 50/60Hz			
Cooling <sup>1</sup>	Capacity	kW	1.5	2.2	2.8	3.6
		kBtu/h	5.1	7.5	9.6	12.3
	Power input	W	18	21	24	27
Heating <sup>2</sup>	Capacity	kW	1.7	2.4	3.2	4
		kBtu/h	5.8	8.2	10.9	13.6
	Power input	W	18	21	24	27
Air flow rate <sup>3</sup>		m <sup>3</sup> /h	460/440/420/400/380/360/340	500/470/440/410/390/370/340	540/510/470/430/400/370/340	580/540/500/460/420/380/340
Sound pressure level		dB(A)	32/31/30/30/29/28/27	33/32/31/30/29/28/27	35/34/33/32/31/30/28	37/36/34/33/31/30/28
Sound power level		dB(A)	45/44/43/43/42/41/40	46/45/44/43/42/41/40	50/49/48/47/46/44/42	54/53/51/50/48/46/44
Unit	Net dimensions (W×H×D)	mm	750×295×265	750×295×265	750×295×265	750×295×265
	Packed dimensions (W×H×D)	mm	875×385×360	875×385×360	875×385×360	875×385×360
	Net/Gross weight	kg	9/11.5	9/11.5	10/12.5	10/12.5
Refrigerant type			R410A/R32			
Pipe connections	Liquid/Gas pipe	mm	Ø6.35/Ø12.7	Ø6.35/Ø12.7	Ø6.35/Ø12.7	Ø6.35/Ø12.7
	Drain pipe	mm	OD Ø16	OD Ø16	OD Ø16	OD Ø16